



TERMOPLAST

TRP Product line

Find out more at termoplast.ro/en/home



Headquarters and Factory
St. Aleea Plopilor no.1
Roman, Romania



www.termoplast.ro/en/home



[termoplastromania](https://www.facebook.com/termoplastromania)

| EUROSLIDE | TILTABLE | SLIDING ON A PARALLEL PLANE | | CHARACTERISTICS | HST (SLIDING LIFT) | SYNEGO SLIDE |
|----------------------------|----------------------------|--|--------|-----------------------------------|-----------------------------|---|
| REHAU | REHAU | REHAU | SCHÜCO | | REHAU | REHAU |
| Euroslide | Synego 80 | All series | | Profile manufacturer | Geneo | Synego 80 |
| >2.4 | >1.1 | 0.84 - 1.3 | | Series type | 1.3 - 1.8 | > 1.3 |
| | | | | Thermal coefficient Uf (w/m2K) | | |
| 70-80 | 80 | 70 / 80 / 82 / 86 | | Frame depth (mm) | 203 | 156 |
| 2 brush seals | 2 | 2/3 | | Number of frame seals | 2 | 1 |
| 100 | 50 | 200 | | Maximum weight on sash(kg) | 400 | 250 |
| 2400 white / 2150 coloured | 2400 white / 2400 coloured | 2400 white/2200 coloured(70&Synego) 2700 white/2600 coloured(Geneo) | | Maximum height (mm) | 2700 white / 2600 coloured | 2500 white / 2300 coloured |
| 4000 white / 3000 coloured | 4000 white / 3000 coloured | 4000 white/ 3000 coloured | | Maximum frame length (mm) | 10000 white / 6800 coloured | 4000 white welding or mechanical joining 3000 coloured welding; 4000 coloured(mechanical joining) |
| 1400 white / 1300 coloured | 4000 white / 3000 coloured | 1600 white/1400 coloured(70&Synego) 2000 white/2000 coloured(Geneo) | | Maximum sash length (mm) | 3000 white / 2600 coloured | 2000 white / 2000 coloured |
| straight | straight | straight / rounded / faceted | | Sash design | straight | straight |
| 1.5 - 2.5 | 2 | 1.5 - 2.5 | | Fixture (mm) | 1.5 - 2.5 | 1.5 - 2.5 |
| | | | | | | |
| white | white | white | | Base body colored | white | white |
| grey | white, grey, brown | white, grey, brown | | Seal colored on white body | grey | grey |
| | | | | | | |
| plus 5-12 days** | plus 8 -15 days** | plus 2-5 days ** | | Standard colours* | plus 5-10 days** | plus 5-10 days** |
| plus 5-12 days** | plus 8 -15 days** | plus 5-12 days** | | Non-standard colours | plus 5-12 days** | plus 5-12 days** |
| classic | classic/invisible | classic/invisible | | Welding technology type | classic/invisible | classic/invisible |
| — | — | plus 2-5 days for Rehau** | | Anthracite grey aluminium plating | plus 3-5 days** | — |
| — | — | plus 15 - 25 days | | Aluminium plating other colours | plus 15-25 days | — |
| | | | | | | |
| 30-32 | 46 | 40-45 | | Soundproofing | 40-45 | up to 43 |
| 24 | 50 | 24 - 52 | | Glazing thickness (mm) | 24 / 36 / 44 / 52 | 34 / 42 / 50 |
| 2 | 2/3 | 2/3 | | Sheets of glass | 2/3 | 2/3 |
| up to RC1 | up to RC3 | up to RC3 (Rehau) / RC2 (Schüco) | | Burglary protection | up to RC2 | up to RC2 |

*Standard colours: walnut, anthracite grey, smooth anthracite grey, golden oak, weiss bianco, mooriche, black.

**Number of days in addition to the standard delivery time.

| CHARACTERISTICS | EURO 70 | CORONA CT70 | SYNEGO 80 | LIVING 82 | GENEO 86 |
|---|-------------------------------|---------------------------------|-------------------------------|---------------------------------|----------------------------------|
| Profile manufacturer | REHAU | SCHÜCO | REHAU | SCHÜCO | REHAU |
| Profile materials | PVC | PVC | PVC | PVC | RAU FIPRO |
| Profile thermal coefficient Uf (w/m²K) | 1.3 | 1.3 | 1.0 | >0.96 | >0.79 |
| Frame depth (mm) | 70 | 70 | 80 | 82 | 86 |
| Frame height (mm) | 64 / 68 | 68 | 72 | 70 | 72 / 86 |
| Number of sash rooms | 5 | 5 | 6 | 7 | 6 |
| Number of frame rooms | 5 | 5 | 7 | 7 | 6 |
| Number of frame seals | 2 | 2 | 3 | 3 | 3 |
| Window sash design | Straight/Rounded | Straight/Rounded | Straight | Straight | Straight |
| Slim sash | – | Da | – | – | – |
| Renovation frame on white body (mm) | 40 / 60 | 30 / 58 | 40 | – | – |
| Renovation frame on grey body (mm) | – | 30 / 58 | 40 | – | – |
| Renovation frame on Brown Body (mm) | – | – | 40 | – | – |
| Renovation frame on caramel body (mm) | – | 30 / 58 | – | – | – |
| Clip-on wing (mm) | 40 / 60 | 50 | 40 / 60 | 50 | 40 / 60 |
| Thermomodule | – | – | – | – | Da |
| Fixture (mm) | 1.5 / 2 / 2.5 | 1.5 / 2 | 1.5 / 2 / 2.5 | 1.5 / 2 | 1.5 / 2 / 2.5 |
| PVC moulding type | Straight/Round | Straight/Round | Straight/Round | Straight | Straight |
| Base body colour | white / grey / brown | white / grey / caramel | white / grey / brown | white / grey | white / (grey, brown, caramel)** |
| Garnish colour on white body | grey | grey | grey | grey, black | grey |
| COLOURS | | | | | |
| White - anthracite grey / anthracite grey | on white body / grey body | on white body / grey body * | on white body / grey body | on white body / grey body* | on white body / grey body * |
| White - anthracite grey glossy/anthracite grey glossy | on white body / brown body* | on white body / grey body | on white body / brown body* | on white body / grey body | on white body* |
| Walnut | on brown body | on grey body | on brown body | on grey body | on brown body* |
| Golden Oak | on brown body | on caramel body | on brown body | on grey body | on caramel body* |
| Weiss bianco | on white body | on white body | on white body* | on white body | on white body* |
| Mooreiche, black | on brown body | on grey body* | on brown body | on grey body* | on brown body* |
| Non-standard colours on stock body | on white body / grey / brown* | on white body / grey / caramel* | on white body / grey / brown* | on white body / grey* | on white body* |
| Welding technology type | classic/invisible | classic/invisible/HFL | classic/invisible | classic/invisible | classic/invisible |
| Anthracite grey aluminium plating | – | – | plus 3 - 5 days** | – | – |
| Aluminium plating other colours | – | – | plus 15 - 25 days | – | – |
| Handles | Hoppe | Schüco, Hoppe | Hoppe | Schüco, Hoppe | Hoppe |
| Types of aluminium threshold (mm) | 20 | 20 | 20 | 20 | 20 |
| Extensions (mm)* and multiples | 20 / 40 / 60 | 25 / 50 / 60 | 20 / 45 / 60 / 100 | 30 / 50 | 20 / 40 / 60 |
| Mounting height (mm) | 30 | 30 | 30 | Schüco 60 with seal and barrier | 30 |
| Arched frames | plus 5 - 8 days* | plus 5 - 8 days* | plus 5 - 8 days* | plus 15 - 25 days* | plus 5 - 8 days* |
| Soundproofing | up to 45 dB | up to 46 dB | up to 46 dB | up to 47 dB | up to 47 dB |
| Glazing thickness (mm) | 24 / 32 / 40 | 24 / 28 / 40 | 34 / 42 / 50 | 28 / 44 / 52 | 44 / 52 |
| Sheets of glass | 2/3 | 2/3 | 2/3 | 2/3 | 3 |
| Burglary protection | up to RC3 | up to RC2 | up to RC3 | up to RC2 | up to RC3 |

*Delivery times 3-12 days more than standard

**Details at TRP consultants